

Green Marine
Europe
Environmental
Program

2022



Performance
Indicators for
Ship owners

Copyright © 2022 Green Marine Management Corporation
All rights reserved. Reproduction and distribution of the Green Marine
Europe Environmental Program are strictly prohibited.

Table of contents

1. AQUATIC INVASIVE SPECIES	3
2. POLLUTANT AIR EMISSIONS - SO _x AND PM.....	5
3. POLLUTANT AIR EMISSIONS - NO _x	7
4. GREENHOUSE GAS EMISSIONS.....	8
5. OILY DISCHARGE.....	10
6. WASTE MANAGEMENT	12
7. UNDERWATER NOISE.....	14
8. SHIP RECYCLING	16

1. AQUATIC INVASIVE SPECIES

OBJECTIVE: Reduce the risk of introducing and propagating aquatic invasive organisms and pathogens associated with ballast water discharges and biofouling.

APPLICABILITY: This indicator is only applicable for fleets that regularly manage ballast water.

Note: “Regularly” excludes exceptional transits like a repositioning cruise, sea trials or some construction condition. It would still allow non-applicability for newer ballast configurations like flow-through that don’t traditionally carry and discharge.

Note: Acronym BWMS is equivalent to BWTS

LEVEL 1
Monitoring of regulations
LEVEL 2
<p>2.1. Minimize or, whenever possible, avoid uptake of ballast water in the following conditions:</p> <ul style="list-style-type: none"> - In shallow water; - In areas close to sewage outflows; - In areas with known epidemics or infestations; - In areas where dredging operations are underway; - In areas where tidal flushing is poor; - In areas identified by regulatory authorities. <p><u>Note:</u> These measures should include any specific regulations applicable in ports or transit areas.</p> <p>2.2. Uptake only the minimum amount of ballast water required to safely depart the dock, and complete ballasting operations in deeper waters (while always ensuring the vessel’s safety).</p> <p>2.3. Develop and implement voluntary preventive measures if EU national / EU port authorities determine that a harmful species has established itself in a particular port.</p> <p>2.4. Periodically inspect vessels’ hulls, including niche areas, such as sea chests, propeller thrusters, keels, rudders, and dry dock support strips. <u>Note:</u> Refer to 2011 IMO Biofouling Guidelines Sections 1.4, 7.2, 7.3, and 7.4. A copy can be found in the Members section of the Green Marine website.</p> <p>2.5. If needed, remove biofouling organisms from the hull, propellers, stern tube, sea chests, and other wetted portions of a vessel. <u>Note:</u> Cleaning with capture is suggested if biofouling covers over 15% of the wetted surfaces. At 15% coverage, the vessel is considered extensively fouled. Diagrams to help estimate percent coverage can be found in the Members section of the Green Marine website.</p> <p>2.6. For each vessel, keep a record book on details of all inspections and biofouling management measures undertaken on the ship. <u>Note:</u> A template of such a record book can be found in the Members section of the Green Marine website.</p> <p>2.7. <u>Shipowners operating in domestic/local waters (vessels not equipped with a BWMS):</u> If feasible and safe, conduct water ballast exchange during coastal vessel trade prior to re-entering the next port. <u>Note:</u> Domestic/local waters trade is defined as "a movement of cargo and passengers between coastal ports and within EEZ waters.</p>

LEVEL 3

3.1. Maintain a Ballast Water Management plan and Biofouling Management plan for each vessel which includes all the best practices required to achieve Level 2. Have a policy to support scientific research (3.2).

Note: A Biofouling Management plan template can be found in the Members section of the Green Marine website.

3.2. Support scientific research on ballast water or biofouling by providing access to ships for sampling by governmental and research groups or by participating in an expert working group.

Note: It is not necessary to actively participate in the research program in order to fulfill this criterion.

Only for vessels without BWMS:

3.3. Complete and maintain an annual inventory to evaluate the amount of ballast water taken and discharged by the company's ships by origin/destination.

Note: See Annex 1-A.

Only for vessels with a BWMS:

3.4. Produce an annual internal log showing any cases of ballast water treatment system malfunctioning. For such cases, include root cause(s) and preventive action(s) taken.

Note: This log has to include any PSC deficiency concerning BWMS.

For vessels with antifouling or fouling release coating:

3.5. Within dry-docking specifications, select coating with effective coating lifespan in line with the schedule for next dry-docking and anticipate operational wear, such as contact with lock walls or abrasive cleaning.

Note: The effective coating lifespan is determined by the manufacturer based on the vessel-specific application scheme (e.g., coating thickness); it is the age of an anti-fouling coating after which the coating is no longer expected to satisfactorily prevent or deter the attachment and growth of biofouling organisms.

LEVEL 4

Fulfill one of the following 2 criteria:

4.1 Actively participate in research on reducing the risk of AIS introduction and spread associated with ballast water operations and discharges. For example, partner with an academic institution, technology developer, innovation accelerator, related PhD funding, or government agency.

OR

4.2. Actively participate in research for eco-friendly biofouling paints and antifouling systems and on reducing the risk of AIS via biofouling, for example - autonomous underwater cleaning or underwater cleaning reclamation (vacuum or other control technologies).

Note: Active participation is defined as the provision of support by the company, whether through financial means, human resources or equipment and can include an experimental shipboard trial.

LEVEL 5

5.1. Install and use a ballast water treatment system on one or several of the company's vessels. And, for each installed and in-use system, adopt contingency measures, as per MEPC 71/WP.9 Annex 4.

Note: See the "Links to Ballast water Regulations" document in the Members section of the Green Marine website for reference and links to regulations.

AND fulfill one of the following 3 criteria:

5.2. For each installed BWMS, conduct a ballast water management system commissioning test for biological efficacy.

Use the international Maritime Organization (IMO) Marine Environment Protection Committee (MEPC) Circular 70 (BWM.2/CIRC 70/Rev.1) as the basis for sampling and analysis. The document can be found in the Members section of the Green Marine website.

OR

1.5.3. Purchase or install a compliance monitoring device and conduct annual self-monitoring of ballast water discharges for each installed BWMS.

OR

5.4. Submit data on the use of the BWMS to the ship owner's flag State and shipowners' association (such as ECSA, Armateurs de France, etc.) to contribute to the IMO Experience Building Phase.

2. POLLUTANT AIR EMISSIONS - SO_x AND PM

OBJECTIVE: Reduce pollutant air emissions of sulphur oxides (SO_x) and particulate matter (PM).

LEVEL 1
Monitoring of regulations
LEVEL 2
<p>2.1. Implement a systematic control policy for documenting fuel (bunker notes). <u>Note:</u> Bunker notes must be conserved, and annual consumption notes must be kept for each ship.</p> <p>2.2. Use climatology and weather forecasting to take advantage of tidal currents and avoid storms. Plan voyages to reduce running hours and idling time.</p> <p>2.3. Optimize trim for fuel efficiency when loading ships and barges.</p> <p>2.4. Follow voluntary slow speed measures in specific zones, as identified by port or governmental authority. <u>Note:</u> the identified zones are Particularly Sensitive Sea Areas (PSSA): http://www.imo.org/en/OurWork/Environment/PSSAs/Pages/Default.aspx</p> <p>2.5. Implement a preventive engine maintenance system in order to optimize performance.</p> <p>2.6. Identify optimal engine speed or engine load for fuel efficiency. Inform crew and ensure awareness of this optimal 'economic' speed or engine load. Transit at this speed or load to the extent practicable.</p> <p>2.7. Implement a replacement program for LED or other energy efficiency light upgrades.</p> <p><u>Tugs Only:</u> 2.8. Reduce tug idling with dispatch scheduling and/or provide tie-up locations where awaiting tow or escort.</p>
LEVEL 3
<p>3.1. Complete an annual inventory of SO_x and particulate matter (PM) emissions for all the company's ships. <u>Note:</u> See Annexes 2-A, 2-B, and 2-D.</p> <p>3.2. The average sulphur content by mass of the total amount of fuel consumed annually by all of the company's vessels is less than 0.45%. <u>Note:</u> Fuel sulphur limit is 0.1 % within an ECA and 0.5 % outside ECAs. <u>Note:</u> ship owners can use equipment or alternative fuel allowing for the attainment of the same level of sulphur emissions as above.</p> <p>Fulfill one of the following two criteria:</p> <p>3.3. Reduce SO_x emissions in berth by using alternatives to traditional marine fossil fuel, i.e. cold ironing (if available at docks), LNG, Biogas, Biofuel, H₂, fuel cell, batteries, wind or solar energy as an auxiliary energy, or EGCS. Those measures should be implemented on at least 10% of the fleet (representing 7% or more of the tonnage).</p> <p>OR</p> <p>3.4 Reduce SO_x in Port/Berth by using a fuel with sulphur content equal to less than 0,1%, including for every call, including short calls (less than 2 hours) on 100% of the fleet <u>Note:</u> ship owners can use equipment or alternative fuel allowing for the attainment of the same level of sulphur emissions as above.</p>

LEVEL 4

4.1. The average sulphur content by mass of the total amount of fuel consumed annually by all of the company's vessels is less than 0.35%.

Note: Fuel sulphur limit is 0.1 % within an ECA and 0.5 % outside ECAs.

Note: ship owners can use equipment or alternative fuel allowing for the attainment of the same level of sulphur emissions as above.

4.2. Reduce SO_x emissions in berth by using alternatives to traditional marine fossil fuel, i.e. cold ironing (if available at docks), LNG, Biogas, Biofuel, H₂, fuel cell, batteries, wind or solar energy as an auxiliary energy, or EGCS. Those measures should be implemented on at least 25% of the fleet (representing 15% or more of the tonnage).

AND (all ship owners), fulfill one of the following 2 criteria:

4.3. Sample PM emissions for one of the fleet's main engine types (slow-speed, medium-speed, high-speed, gas or steam turbine).

Note: Sampling must be repeated every five (5) years. The sampling test plan must be consistent within the fleet, comparable with prior tests, and a recognized methodology, such as ISO 8178 or 40 CFR 51 Appendix M and 40 CFR 60 Appendix A.

OR

4.4. Actively participate in research and development on reducing the impact of SO_x and PM emissions, for example – improving inventory tools, developing hybrid or blended fuels, or conducting a pilot project on emission reduction technologies.

Note: Active participation is defined as the provision of support by the company, whether through financial means, human resources or equipment and can include an experimental shipboard trial.

LEVEL 5

5.1. The average sulphur content by mass of the total amount of fuel consumed annually by all of the company's vessels is less than 0.25%.

Note: Fuel sulphur limit is 0.1 % within an ECA and 0.5 % outside ECAs.

Note: ship owners can use equipment or alternative fuel allowing for the attainment of the same level of sulphur emissions as above.

5.2. Reduce SO_x emissions in berth by using alternatives to traditional marine fossil fuel, i.e. cold-ironing (if available at docks), LNG, Biogas, Biofuel, H₂, fuel cell, batteries, wind or solar energy as an auxiliary energy, or only closed-loop EGCS. Those measures should be implemented on at least 50%+1 of the fleet (representing 30% or more of the tonnage).

5.3. On board one or more of the company's owned ships, compared to no treatment, achieve a 75 % or greater reduction of PM emissions per ship by (i) applying pre-treatment and on-engine measures, (ii) applying after-treatment measures, such as a diesel particulate filter (DPF), diesel oxidation catalysts (DOCs), or other exhaust gas cleaning system (EGCS), (iii) using wind propulsion, or by (iv) using LNG or other energy-solutions having low Sox & PM emissions.

5.4. In the polar zone, vessels will not use or carry any heavy fuel or VLSFO/ULSFO.

3. POLLUTANT AIR EMISSIONS - NO_x

OBJECTIVE: Reduce pollutant air emissions of nitrogen oxides (NO_x).

LEVEL 1
Monitoring of regulations
LEVEL 2
<p><i>The use of specialized software or of any other verifiable procedure can serve as evidence that the practices below have been implemented.</i></p> <p>2.1. Implement a systematic control policy for documenting fuel (bunker notes). <u>Note:</u> Bunker notes must be conserved, and annual consumption notes must be kept for each ship.</p> <p>2.2. Use climatology and weather forecasting to take advantage of tidal currents and avoid storms. Plan voyages to reduce running hours and idling time.</p> <p>2.3. Optimize trim for fuel efficiency when loading ships and barges.</p> <p>2.4. Follow voluntary slow speed measures in specific zones, as identified by port or governmental authority. <u>Note:</u> the identified zones are Particularly Sensitive Sea Areas (PSSA) http://www.imo.org/en/OurWork/Environment/PSSAs/Pages/Default.aspx</p> <p>2.5. Implement a preventive engine maintenance system in order to optimize performance.</p> <p>2.6. Identify optimal engine speed or engine load for fuel efficiency. Inform crew and ensure awareness of this optimal 'economic' speed or engine load. Transit at this speed or load to the extent practicable.</p> <p>2.7. Implement a replacement program for LED or other energy efficiency light upgrades.</p> <p><u>Tugs Only:</u></p> <p>2.8. Reduce tug idling with dispatch scheduling and/or provide tie-up locations where awaiting tow or escort.</p>
LEVEL 3
<p>3.1. Complete an annual inventory of NO_x emissions for all the company's ships. <u>Note:</u> See Annexes 2-C and 2-D.</p>
LEVEL 4
<p>4.1. Conduct sampling of NO_x emissions on at least one of the company's ships within the last five (5) years. The sampling test plan must be consistent within the fleet, comparable with prior tests, and a recognized methodology, such as ISO 8178 or IMO NO_x Technical Code 2008.</p> <p>4.2. On board one or more of the company's owned ships, install a higher tier engine than required or use and maintain on-engine or after-treatment NO_x emission reduction technologies, like selective catalytic reduction (SCR) or exhaust gas recirculation (EGR), or methods that result in a 15% reduction of NO_x emissions below the permitted limits. <u>Note:</u> Permitted limits are published in the document 'NO_x emission permitted limits' in the Members section of the Green Marine website.</p>
LEVEL 5
<p>Fulfill one of the following 2 criteria:</p> <p>5.1. On board the majority (50%+1 representing at least 30% of the gross tonnage) of the company's owned ships, install a higher tier engine than required or use and maintain on-engine or after-treatment NO_x emission reduction technologies or methods that result in a 15 % reduction of NO_x emissions per ship below the permitted limits. <u>Note:</u> Permitted limits are published in the document 'NO_x emission permitted limits' in the Members section of the Green Marine website. <u>Note:</u> Under the designation of these NECA's, marine diesel engines installed on board ships built on or after 1 January 2021 and operating in the North Sea and Baltic Sea should comply with the Tier III NO_x emission limits</p> <p>OR</p> <p>5.2. On board one or more of the company's owned ships, achieve a 50% or greater reduction of NO_x emissions per ship below the permitted limits by installing a higher tier engine than required or by using and maintaining NO_x emission reduction technologies.</p>

4. GREENHOUSE GAS EMISSIONS

OBJECTIVE: Reduce greenhouse gas (GHG) emissions.

LEVEL 1
Monitoring of regulations
LEVEL 2
<p><i>The use of specialized software or other verifiable procedure can serve as evidence that the practices below have been implemented.</i></p> <p>2.1. Implement a systematic control policy for documenting fuel (bunker notes). <u>Note:</u> Bunker notes must be retained, and annual consumption notes must be kept for each ship.</p> <p>2.2. Use climatology and weather forecasting to take advantage of tidal currents and avoid storms. Plan voyages to reduce running hours and idling time.</p> <p>2.3. Optimize trim for fuel efficiency when loading ships and barges.</p> <p>2.4. Follow voluntary slow speed measures in specific zones, as identified by port or governmental authority. <u>Note:</u> the identified zones are Particularly Sensitive Sea Areas (PSSA): http://www.imo.org/en/OurWork/Environment/PSSAs/Pages/Default.aspx</p> <p>2.5. Implement a preventive engine maintenance system to optimize performance.</p> <p>2.6. Identify optimal engine speed or engine load for fuel efficiency. Inform crew and ensure awareness of this optimal 'economic' speed and/or engine load. Transit at this speed to the extent practicable.</p> <p>2.7. Implement a replacement program for LED or other energy efficiency light upgrades.</p> <p>2.8. Implement an onboard policy to put on standby or stop the unused devices and equipment, except those linked to safety or environmental protection.</p> <p><u>Tugs Only:</u> 2.9. Reduce tug idling with dispatch scheduling and/or provide tie-up locations where awaiting tow or escort.</p>
LEVEL 3
<p>3.1. Complete and disclose an annual GHG emissions inventory (totals and intensity) for the company's entire fleet, including voyages outside Europe. <u>Note:</u> For more information on the calculation of GHG emissions, see Annex 3-B and the Commission Implementing Regulation (EU) 2016/1927 on templates for monitoring plans, emissions reports and documents of compliance pursuant to the EU MRV Regulation https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32016R1927&from=EN</p> <p>3.2. Adopt an Energy Performance Plan that has quantifiable objectives and that formally incorporates the best practices required for achieving Level 2. <u>Note:</u> See Annex 3-C.</p> <p>3.3. Based on the inventory made in criterion 4.3.1, set a strategic objective aiming at a 40% reduction of GHG per transport work (or other appropriate normalizers) by 2030 since 2018 and full decarbonization of the fleet by 2050. <u>Note:</u> See annex 3-B for methodology.</p>

LEVEL 4

4.1. Based on the inventory made in criterion 4.3.1, achieve an annual average reduction in GHG intensity (GHG emissions per ton or passenger or cubic meter or deadweight-nautical mile or per hour- for tugs or other non-cargo ships) of 2.3% since 2018.

Note: For more information on the calculation of GHG emissions, see Annex 3-B and the Commission Implementing Regulation (EU) 2016/1927 on templates for monitoring plans, emissions reports and documents of compliance pursuant to the EU MRV Regulation <https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32016R1927&from=EN>

Note: As per present information (10/2020), for the 2030 target, the IMO trajectory reduction should be of 1.8% annually on the 2008 basis.

OR

If criterion 4.1 is not applicable, for the specific cases of ship owners that did not have data in 2018 and/or already invested in a low carbon fleet that has a consistent impact on the GHG performance of the fleet (see annex 3-A for "low carbon" definition).

4.2. Achieve an average annual GHG intensity per transport work of their vessel(s) equal to or below the EEOI value as calculated according to the three different options to assess vessel GHG performance as described in Annex 3-D (level 4).

Note: Other ship owners should comply with criterion 4.1.

AND

4.3. Define an action plan towards a 40% GHG reduction per transport work by 2030.

LEVEL 5

5.1. Based on the inventory made in criterion 4.3.1, achieve an annual average reduction in GHG intensity (GHG emissions per ton or passenger or cubic meter or a deadweight-nautical mile or per hour for tugs or other non-cargo ships) of 3.3% since 2018.

Note: For more information on the calculation of GHG emissions, see Annex 3-B and the Commission Implementing Regulation (EU) 2016/1927 on templates for monitoring plans, emissions reports and documents of compliance pursuant to the EU MRV Regulation <https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32016R1927&from=EN>

Note: As per present information (10/2020), for the 2030 target, the IMO trajectory reduction should be of 1.8% annually on the 2008 basis.

OR

If criterion 5.1 is not applicable, for the specific cases of ship owners that did not have data in 2018 and/or already invested in a low carbon fleet that has a consistent impact on the GHG performance of the fleet (see annex 3-A for "low carbon" definition).

5.2. Achieve an average annual GHG intensity per transport work of their vessel(s) equal to or below the EEOI value as calculated according to the three different options to assess vessel GHG performance as described in Annex 3-D (level 5).

Note: Other ship owners should comply with criterion 5.1.

AND fulfill one of the following 3 criteria:

5.3. Actively participate in and provide funding for a study and/or project with shipping decarbonization objectives reachable before 2030, such as:

- zero-emission or low emission vessel(s) with the objective to build a demonstration vessel by 2028
- low emission alternative fuel/energy or biofuel (liquid or gas) production
- Any other project with shipping decarbonization objectives (such as those referenced by the Getting to Zero Coalition and Zero Emissions Waterborne Transport)

OR

5.4. Acquire and/or build a low carbon emission vessel that includes at least a 30% emission reduction on laden voyages (propulsion and auxiliary needs). At least one vessel in the fleet should be equipped with low carbon propulsion means such as wind or use alternative fuels/energy. Note: see Annex 3-A for definitions.

OR

5.5. For at least 75% of the vessels in the fleet,

Adopt an action plan demonstrating that either the average speed or engine settings will meet the parameters prescribed in Annex 3-F for Maximum AVR speed. Demonstrate that engine efficiency optimization settings were defined and implemented (e.g., optimum for speed, load setting, number of running engines, etc.).

Note: See Annex 3-F

AND (OPTIONAL)

5.6. In addition to the direct GHG emissions annual inventory corresponding to 4.3.1, calculate an annual estimate of total indirect emissions for the energy/fuels used for the company's fleet's entire (Well-to-Wake/Propeller) emissions footprint. These indirect GHG emissions include those from the purchase of electricity and for transporting the fuels to the vessels (Well to Tank/upstream emissions).

Note: For more information on the estimation of these indirect GHG emissions, see Annex 3-E; and for more information on definitions, see Annex 3-A.

5. OILY DISCHARGE

OBJECTIVE: Minimize risk of oily water discharges.

LEVEL 1
Monitoring of regulations
LEVEL 2
<p>Vessels using an Oily Water Separator (OWS) on board:</p> <p>Implementation of 7 of the following 10 best practices on all company ships:</p> <p>2.1. Give staff proper training on bilge water management.</p> <p>2.2. Ensure performance of each oily water separator (OWS) by:</p> <ul style="list-style-type: none"> a) Conduct annual calibration of the oil content meter; or b) Sample treated water monthly and have it analyzed by an accredited lab; or c) Use a secondary calibrated monitoring unit (e.g., white box). <p>2.3. Periodically test oil content alarm prior to operating the oily water separator and, in any case, at least once a month if the equipment is not used.</p> <p>2.4. Use seals or locks on all overboard discharge valves.</p> <p>2.5. Post signs in the vicinity to clearly indicate who is responsible for opening any OWS overboard discharge valves, operating oily water separation equipment, and for oil transfer procedures.</p> <p>2.6. Lock out or seal the oil content meter so that the calibration cannot be tampered with.</p> <p>2.7. Maintain proper coordination with the navigation bridge when opening the overboard discharge valve so a designated officer can also record the activity and the vessel's position.</p> <p>2.8. When feasible, only operate the oily water separator during the daytime.</p> <p>2.9. Regularly clean the applicable bilges and remove any solid material that may reduce the performance of the OWS.</p> <p>2.10. Reduce as much as possible the use of emulsifying cleaners and agents that can degrade the performance of the OWS.</p> <p>Vessels NOT using an Oily Water Separator (OWS) on board (even if installed):</p> <p>Implementation of 5 of the following 8 best practices on all company's vessels:</p> <p>2.11. Regularly inspect and perform preventative maintenance of equipment using oil (engine, burners, pumps, pipes, heaters, filters, etc.) or water (condensers, boilers, pumps, pipes, etc.) to prevent leaks. Note: Inspections should be done at least in line with manufacturer recommendations.</p> <p>2.12. Regularly assess the condition and maintain stern tube seals and bearings to prevent water from entering. Note: Inspections should be done at least annually.</p> <p>2.13. Stop oil or water leaks in the engine room as soon as possible.</p> <p>2.14. Clean up oil and water spills as soon as possible after maintenance and repair operations.</p> <p>2.15. Maintain clean, dry bilges</p> <p>2.16. Post signs in the vicinity to clearly indicate who is responsible for bilge water transfer procedures.</p> <p>2.17. Give staff proper training on bilge water management.</p> <p>2.18. Keep available on board oil absorption pads to intervene in case of minor oil spills.</p>

LEVEL 3

3.1. Adopt an Oily Water Management plan that formally incorporates all the best practices itemized in level 2.

Note: See Annex 4-A.

3.2. Complete an annual inventory of quantities of bilge water (produced, treated, discharged to sea and offloaded to shore) and of oil residue (sludge), as applicable, on a vessel-by-vessel basis and for the fleet as a whole.

Note: See Annex 4-B.

3.3. Develop and adhere to environmental procurement guidelines for cleaning products to be used within the engine room, considering third-party certifications*, product content**, and packaging (see the Waste management performance indicator).

*Such as Centre for Environment, Fisheries and Aquaculture Science (Cefas).

**Chlorine, phosphate-free, minimally toxic, etc.

LEVEL 4

Vessels using an Oily Water Separator (OWS) on board:

4.1. Adopt a modernization program for oily water separators and all related control and verification equipment. Systematic application of this policy on all new buildings and all ships undergoing major modifications.

Note: See Annex 4-C.

4.2. For the majority of new builds:

Implement an integrated bilge treatment system such as that defined in the IMO's revised guidelines (MEPC.1/Circ.642, 12 November 2008).

OR

4.3. Vessels built before 2011:

Demonstrate an integrated bilge treatment system approach by respecting the requirements defined in Annex 4-D.

Note: See Annex 4-D.

Vessels NOT using an Oily Water Separator (OWS) on board (even if installed):

4.4 Set reduction or maximum targets (for the fleet as a whole or by vessel category) for bilge water produced.

4.5 Implement effective measures to reduce the quantity of bilge water and sludge produced on 50 % of the company's vessels targeted for reduction.

Examples: Separate drainage systems for water and oil drains, installation of drip trays or coamings under equipment, use less water for maintenance and cleaning, replacement and repair of stern tube seals, etc.).

LEVEL 5

5.1. On all new-build vessels (from January 1st, 2022) fitted with conventional horizontal stern tubes, eliminate the oil-to-water interface by using seawater lubricated bearings or an alternative sealing arrangement. For non-conventional propulsion arrangements, demonstrate best efforts to utilize technologies as they advance to eliminate or reduce the impact of an oil-to-water interface.

Vessels using an Oily Water Separator (OWS) on board:

5.5.2 Do not discharge treated bilge water in sensitive areas.

Note: Sensitive areas mean

- Worldwide Particularly Sensitive Sea Areas (PSSA) and Marine Protected Areas (MPA)
- Indigenous Protected and Conserved Areas (IPCA). For USA/Canada, see https://www3.epa.gov/npdes/pubs/vgp_permit2013.pdf and <https://www.dfo-mpo.gc.ca/oceans/maps-cartes/conservation-eng.html>

For all new builds:

5.3. Implement an integrated bilge treatment system such as that defined in the IMO's revised guidelines (MEPC.1/Circ.642, 12 November 2008).

OR

5.4. Vessels built before 2011:

Demonstrate an integrated bilge treatment system approach by respecting the requirements defined in Annex 4-D.

Note: See Annex 4-D.

Vessels NOT using an Oily Water Separator (OWS) on board (even if installed):

5.5. Implement effective measures to reduce the quantity of bilge water and sludge produced on 75 % of the company's vessels targeted for reduction.

Examples: Separate drainage systems for water and oil drains, installation of drip trays or coamings under equipment, use less water for maintenance and cleaning, replacement and repair of stern tube seals, etc.).

5.6. Demonstrate an annual reduction or negligible (too small to reliably, quantitatively measure) amount of the quantity of bilge water and/or sludge produced (intensity unit is to be determined by the company, e.g. tons/hour of operation).

6. WASTE MANAGEMENT

OBJECTIVE: Reduce ship-generated waste.

APPLICABILITY: This performance indicator only applies to the company's owned vessels.

LEVEL 1
Monitoring of regulations
LEVEL 2
<p>2.1. Equip all of the company's ships with recycling bins and give staff proper training on established user procedures and the waste management hierarchy (reduce, reuse, recycle, recovery, disposal).</p> <p>2.2. Favor suppliers that use less packaging.</p> <p>2.3. Encourage best practices to reduce the use of non-reusable supplies for all types of products. Note: This reduction goal is already a legal obligation for single-use plastic products according to Directive 2019/904 on the reduction of the impact of certain plastic products on the environment. <u>Note:</u> Biodegradable supplies could be considered if there is no other possibility.</p> <p>2.4. No shipboard incineration at port.</p> <p>2.5 Encourage best practices to reduce wasted food on board.</p> <p><u>Applicable only to vessels carrying cargoes, not in bulk and performing regularly consecutive voyages:</u> 2.6. Reuse as much as possible dunnage, lining and packaging material.</p>
LEVEL 3
<p>3.1. Produce an annual inventory of different types of garbage generated in the company's entire fleet and indicate the company's actual garbage management practices. <u>Note:</u> Garbage types refer to the categories defined in MARPOL Annex V, but each company can include additional categories.</p> <p>3.2. Adopt and implement a management plan towards zero single-use plastic on board (if there is a suitable alternative) <u>Note:</u> See Annex 5-B for a list of the single-use plastic items to avoid. <u>Note:</u> Bioplastics are not considered suitable alternatives, as they are not biodegradable.</p> <p>3.3. Adopt and implement a management plan that provides in-house training and raises awareness for crew and ground personnel on waste prevention to facilitate waste reduction, sorting, reuse, possible recycling, and avoiding wasted food.</p> <p><u>Passenger vessels only:</u> 3.4. Implement an awareness campaign for passengers on waste prevention to facilitate waste reduction, reuse, possible recycling, avoiding wasted food. <u>Note:</u> this awareness campaign is already a legal obligation for single-use plastic products according to Directive 2019/904 on the reduction of the impact of certain plastic products on the environment.</p> <p><u>Container ships only:</u> 3.5 Adopt and implement a specific weather routing policy to avoid adverse weather conditions and subsequent potential container loss at sea.</p>
LEVEL 4
<p>4.1. Develop and implement a garbage management strategy with defined targets and specific measures to reduce garbage and wasted food, increase recycling, and ultimately target zero discharge at sea. <u>Note:</u> See Annex 5-A</p> <p><u>Ships using Exhaust Gas Cleaning Systems (EGCS) only:</u> 4.2. Discharge waste generated by EGCS ashore via service providers approved by the local port authority.</p> <p><u>Container ships only:</u> 4.3. Facilitate transparent, online public quarterly reporting of containers lost at sea. Reporting should include information on the vessel, its voyage, the location of the loss, and the total number of containers lost.</p>

LEVEL 5

5.1. Demonstrate continual improvement by achieving targets defined in the garbage management strategy.

Note: See annex 5-C for more information on plastic materials.

5.2. From January 1st, 2022, EGCS should be used only in closed-loop mode:

- for all new building vessels ordered after January 1st, 2022 (date of contract) with an EGCS
- for vessels retrofitted after this date (date of retrofitting contract) with an EGCS.

Container ships only:

5.3 In the quarterly public report from criterion 4.3, disclose whether containers lost at sea contained dangerous goods (as per IMDG code) or plastic pellets.

AND

5.4 Actively participate in workshops and/or research focused on the avoidance of container loss at sea, including topics such as: lashing improvement, container loss detection systems, etc.).

7. UNDERWATER NOISE

OBJECTIVE

Reduce underwater noise made by ship operations to reduce impacts to marine mammals.

NOTES:

- Green Marine Europe recognizes that underwater noise may potentially impact a broader range of aquatic species other than just marine mammals. While the initial objective of this indicator covers marine mammals, future development of this Performance Indicator may expand its scope.
- Green Marine Europe recognizes that for most ships, under most operational conditions, cavitation is the main source of underwater noise.
- Applicable only for vessels transiting in salt water.

LEVEL 1
Monitoring of regulations
LEVEL 2
<p>2.1. Conduct regular hull cleaning and propeller blade maintenance. The participant must keep a record of these actions for each vessel in their fleet. <u>Note:</u> Hull cleaning and propeller maintenance should at least be done during dry dock.</p> <p>2.2. Review the list of sensitive areas in Canadian, US and EU waters to determine whether the participant's vessels transit through or have operations in such areas. Ensure that this information is communicated to each vessel. <u>Note:</u> See Annex 6-A.</p>
LEVEL 3
<p>3.1. Actively participate in providing whale sighting data in European waters through a logbook, a recognized application such as a European version of the US app Whale Alert or the REPCET system (outside mandatory zones for French ship owners). <u>Note:</u> If sightings are recorded in a logbook, the data should be shared with a recognized central database.</p> <p>3.2. Develop and adopt a Marine Mammal Management plan (MMMP) in order to reduce the potential adverse effects of vessels, especially within known sensitive marine areas, as identified in Criterion 2.2. <u>Note:</u> See Annex 6-B.</p>
LEVEL 4
<p>4.1. Incorporate applicable vessel quieting technologies during retrofits and new vessel construction. <u>Note:</u> Refer to published documents like the IMO and the SNAME MVEP Guidelines, available in the Members section of the Green Marine website. This criterion is applicable only for ship owners ordering/designing new vessels (keel laid after Jan 2018) or conducting retrofits of propulsion systems or other equipment that contributes significantly to underwater noise.</p> <p>AND fulfill one of the following 3 criteria:</p> <p>4.2. Work with ports to estimate relative ship noise levels for at least one vessel in their fleet. It is recommended to start by the oldest vessels of the fleet (by year of construction) or by sisterships.</p> <p>OR</p> <p>4.3. In line with IMO recommendations, estimate relative ship noise levels of at least one vessel in their fleet by using a dedicated hydrophone. It is recommended to start by the oldest vessels of the fleet (by year of construction) or by sisterships. <u>Note:</u> Collaboration with a bioacoustician is essential to obtain reliable data.</p> <p>OR</p> <p>4.4. Support / collaborate on scientific research on underwater noise allowing the estimation of relative ship noise levels for at least one vessel in their fleet.</p> <p>AND fulfill the following criterion:</p> <p>4.5. Determine the cavitation inception speed (CIS) for each vessel in the fleet. <u>Note:</u> This criterion is only applicable for vessels equipped with a Fixed Pitch Propeller (FPP).</p>

LEVEL 5

Fulfill one of the following 3 criteria:

5.1. Work with ports to estimate relative ship noise levels for 15% of the vessels in their fleet representing at least 10% of the gross tonnage, with a minimum of 3 vessels measured. It is recommended to start by the oldest vessels of the fleet (by year of construction) or by sisterships.

OR

5.2. In line with IMO recommendations, estimate relative ship noise levels of 15% of the vessels in their fleet representing at least 10% of the gross tonnage, with a minimum of 3 vessels measured, using a dedicated hydrophone. It is recommended to start by the oldest vessels of the fleet (by year of construction) or by sisterships.

Note: Collaboration with a bioacoustician is essential to obtain reliable data.

OR

5.3. Support / collaborate on scientific research on underwater noise allowing the estimation of relative ship noise levels for 15% of the vessels in their fleet representing at least 10% of the gross tonnage, with a minimum of 3 vessels measured.

AND fulfill the following criterion:

5.4. Proceed to an in-depth analysis of vessel noise footprint on at least one ship in order to identify main noise sources. It is recommended to start by the oldest vessels of the fleet (by year of construction) or by sisterships. Solutions to be identified and implemented to reduce noise output.

Note: ISO 17208-2:2019 underwater noise standard measurement methodology should be used where possible.

8. SHIP RECYCLING

OBJECTIVE

Reduce the effects of ship recycling on human health, safety and the environment.

LEVEL 1
Monitoring of regulations
LEVEL 2
<p>2.1. The participant has a written Policy (or Procedure within a management plan that has been approved by senior management) detailing how their written/documentated commitment will assure that all ships at the end of their economic lives will be recycled in a sustainable, safe, responsible, and environmentally sound manner. The participant's vessel will not change flag at end-of-life to circumvent the EU Ship Recycling Regulation. This Policy or Procedure must be applicable to all of the participants' vessels at the end of their economic life that are not sold for onward trading and are thus sent for recycling. <u>Note:</u> At level 2, the policy /procedure does not need to be made public. <u>Note:</u> See Annex 7-A explaining main requirements and how they are interconnected: Basel Convention, EU Waste Shipment Regulation, EU Ship Recycling Regulation.</p> <p>2.2 Develop Part 1 of an Inventory of Hazardous Materials (IHM) for all new builds (not flying EU flag) that meets the requirements set out in the EU SRR & Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships and is certified as such by a flag or recognized RO. <u>Note:</u> EU SRR is mandatory for all EU Flag new build vessels. <u>Note:</u> If the participant has no new builds on order, they must have at minimum an internal written policy /procedure stating their intentions to develop an IHMs for all new builds, should any vessels be ordered in the future.</p> <p>2.3. Adopt a formal plan to develop Part 1 of an IHM for all Not flying EU Flag existing vessels which are not calling EU ports. <u>Note:</u> EU SRR is mandatory for all Existing EU Flag vessels or calling EU ports as of 01/01/2021.</p> <p>2.4 In accordance with the IHM plan created in level 2.3, develop Part 1 of an IHM for at least one existing vessel Not flying EU Flag and which are not calling EU ports. IHM must meet the requirements set out in the EU SRR & Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships. <u>Note:</u> EU SRR is mandatory for all Existing EU Flag vessels or calling EU ports as of 01/01/2021. <u>Ship owners who sold a vessel for recycling during year of reporting only:</u></p> <p>2.5. If towing a vessel to a recycling facility, review the tow plan and towing company before making final selection.</p>
LEVEL 3
<p>3.1. Develop a hazardous material removal plan that promotes the substitution of hazardous materials during the maintenance of ships (during layup, repair, dry dock, or as other opportunities present themselves) by less hazardous, or preferably, non-hazardous materials.</p> <p>3.2. In accordance with the IHM plan created according to level 2.3, develop Part 1 of an IHM for at least 25% of existing vessels not flying EU Flag and which are not calling EU ports. Validate for this 25% of vessels not flying EU Flag all IHM with accompanying compliance statements and renew on a 5-year basis. IHM must meet the requirements set out in the EU SRR & Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships. <u>Note:</u> EU SRR is mandatory for all Existing EU Flag vessels or calling EU ports as of 01/01/2021.</p> <p>3.3. The public ship recycling Policy demonstrates the participant's commitment to recycling vessels (not already covered by the EU Ship Recycling Regulation or the EU Waste Shipment Regulation) only in ship recycling facilities located in Basel Convention's Annex VII countries. <u>Note:</u> Annex VII includes Parties and other States which are members of OECD, EC, Liechtenstein. <u>Ship owners who sold a vessel not flying EU flag for recycling during the year of reporting only:</u></p> <p>3.4. When seeking to recycle a vessel, the participant will only tender to (or via broker warranting to use) Ship Recycling Facilities that: a) are currently (and expected to be for the duration of the dismantling) referenced in the EU list of Recycling Facilities. b) Are capable and commit to provide a Certificate of Completion of Recycling. <u>Note:</u> Large commercial seagoing vessels flying the flag of an EU Member State may be recycled only in safe and sound ship recycling facilities included in the European List of ship recycling facilities.</p> <p>3.5. Require the ship recycling facility, through a contractual clause, to provide regular recycling progress reports, from the time of vessel arrival to the time of receiving a Certificate of Completion of Recycling. <u>Note:</u> See Annex 7-B for minimum progress report content requirements. <u>Note:</u> Large commercial seagoing vessels flying the flag of an EU Member State may be recycled only in safe and sound ship recycling facilities included in the European List of ship recycling facilities.</p>

LEVEL 4

4.1. In accordance with the IHM plan created in level 2.3, develop Part 1 of an IHM for at least 50% of vessels Not flying EU Flag and which are not calling EU ports - IHM must meet the requirements set out in the EU SRR & Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships.

Note: EU SRR is mandatory for all Existing EU Flag vessels or calling EU ports as of 01/01/2021.

4.2. Implement the hazardous material removal plan adopted in level 3.

LEVEL 5

5.1. Require all vessels Not flying EU Flag and which are not calling EU ports to have completed Part I of an IHM.

Note: EU SRR is mandatory for all Existing EU Flag vessels or calling EU ports as of 01/01/2021

5.2. Implement a policy upon sale in favour of safe and environmentally sound ship recycling, in line with criteria 3.4.; 3.5 and 4.4, and commit to promote the policy upon sale. No ship that has been sold will have been scrapped within 12 months of the sale (except in case of an accident).

Note: See Annex 7-C for examples of policies on selling owned vessels for further trading.

Ship owners who sold a vessel not flying EU Flag for recycling during year of reporting only:

5.3. Remove all hazardous materials not essential to the vessel's classification, certification, or operation as part of pre-cleaning procedures prior to departure for the recycling facility.

5.4. Hire a third-party auditor to undertake announced and unannounced visits to the recycling facility during the dismantling. The frequency to be agreed upon between the participant and the recycling facility. The "Audit During Recycling" (ADR) will be undertaken on-site involving the participant (or third-party auditor representing the participant) and the recycling facility senior management team. Each ADR report will be shared with the participant and recycling facility.

Note: See Annex 7-D for minimum audit report content requirements.

Note: This is not required if the vessel is recycled in facilities featured in the EU List of approved ship recycling facilities.

Cf link https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=uriserv:OJ.L_.2020.018.01.0006.01.ENG&toc=OJ:L:2020:018:TOC